BWM2 BLUETOOTH IMAGE 1D SCANNER

Product Parameter：

Performance Parameters	Picture Sensor		960*640 COMS		
	Capacity	1D	EAN-8，EAN-13，UPC-A，UPC-E，Code 39，Code 93，Code 128，EAN128，codabar，industrial 2 of 5，Interleave 2 of 5，Matrix 2 of 5，MSI etc。		
	Depth of Field		Tested Code	Minimum	Maximum
			5mil code39	1.5CM	8CM
			13mil EAN13	4CM	23CM
			15mil DM	3CM	14CM
			15mil QR	2CM	13CM
			15MIL PDF417	6CM	18CM
	System Compability		Android，Windows,IOS，Linux		
	Light Source		Wavelength:675nm±3nm high brightness near infrared LED		
	Decode Accuracy		Code 39 5mil		
	Code Available		1D Codes printing on Paper or film or Cellphone		
	Scanning Speed		1300 Times/Second		
	Symbol Contrast		20%		
	Scanning Angle		Horizontal : 72° Vertical：82° Rotated:360°		
	Transmission Range		The open space 15 meters		
	Scan Pattern		Manual key scan、Continuous scan		
	Keyboard support		American		
	Secondary development		Not support		
	Barcode output editing		Support adding prefix and suffixes		
Human-computer	Indicator light		Red&Blue LED:Red charging tips, blue decoding flicker		

	Buzzer	Start Tips，Decoding success tips
	Button	Start ,Trigger scan
Wireless parameters	Wireless Technology	Bluetooth
Environment Parameters	Drop	Design to withstand1.5 M drops to concrete5 times
	Environmental Sealing	IP54
	Working Temperature	-20-55℃
	Conserve Temperature	-20-60℃
	Working Humidity	5-95% Non-Condensed
	Conserve Humidity	5-95% Non-Condensed
	Environment Light	0-120000LUX
Physical Parameters	Net Weight	335g
	Packing Weight	510g
	Data line length	140CM(±3CM)
	Host Size(L*W*H)	167mm* 72mm*85mm
	Packing Size(L*W*H)	185mm*110mm*80mm
	Battery capacity	2000MAH
Certification	CE、FCC、ROHS、IEC60950 、IEC62471、 EN55022、 EN55024、 EN61000-3、 IEC62321 EN60950、 EN60529	