YOKO-980 LASER SCANNING

Product Parameter：

Performance Parameters	Scan Pattern	Continuous scan、Manual key scan	
	Bar code reading speed	1000 Times/Second±2%	
	Minimum Contrast Recognition	Reflectance difference：35%	
	Bit Error Rate	1/50,000	
	Scanning Angle	Horizontal : 72° Vertical：82° Rotated:360°	
	Capacity	EAN-8、EAN-13、EAN-13 2 add-on、 EAN-13 5 add-on、ISSN、ISBN、 UPC-A、UPC-E、Code 39、Code 39 Full ASCII、code93、Code 128、EAN128、Codebar、interleave 2 of 5,etc。	
	System Compability	Linux，Android，Mac(Apple IPad)，Windows XP，Windows VISTA，Windows 7，Windows 8，Windows 10，Windows Server 2003，Windows Server 2008，Windows Server 2010	
	Field	EAN13 5mil	1CM-8CM
		EAN13 8mil	4CM-9CM
		EAN13 11mil	2CM-25CM
		EAN13 14mil	4CM-31CM
		EAN13 28mil	6CM-45CM
	Lamp-house Type	Wavelength ： Red laser is 650nm ± 3nm	
	Keyboard support	Not support multi-language keyboard	
	Secondary development	Not support	
	Barcode output editing	Not support adding prefix and suffixes	
Human-computer interaction	Indicator light	Red&Blue LED:Red charging/ mains tips , blue decoding flicker	
	Buzzer	Start Tips，Decoding success tips	
	Button	Trigger scan	
Environment Parameters	Drop	Design to withstand 1.5M drops to concrete 5 times	
	Environmental Sealing	IP54	
	Working /Conserve Temperature	0-40℃/-20-60℃	
	Working /Conserve Humidity	5-95% Non-Condensed	
	Environment Light	100000LUX	
Physical Parameters	Net Weight	240g	
	Packing Weight	668g	
	Data line length	180CM(±3CM)	
	Host Size(L*W*H)	162*68*83mm	
	Packing Size(L*W*H)	260*230*75mm	

	Communication	433MHZ Wireless launch
	Working voltage	+5VDC±0.25V
	Laser grade standard	National secondary laser safety standard
	Electromagnetic compatibility	CE & FCC DOC compliance